



### MIROFIL 1702 Wood Filler

MIROFIL 1702 is an easy to use, single pack wood filler used to produce a closed pore finish.

#### Product Advantages

- Easy to apply, simple wipe on / wipe off application
- Superior build to achieve that high quality closed pore finish

#### Typical Applications

Caskets, Furniture, Commercial Joinery

**Colour:** Natural (appears white in grain)

**Thinning:** Mix thoroughly with up to 15% MIROSOL 1228

**Application Viscosity:** Thick paste

**Application Methods:** Reduce with MIROSOL 1228, apply with a hessian rag. Apply quickly using a circular motion to fill all voids in the wood grain. Use a fresh rag to wipe excess material off across the grain. Finally, lightly skim over the surface along the grain to remove any surface residue.

Any MIROSTAIN stain or coating may be used over MIROFIL 1702 Wood Filler.

**Drying:** 4 hours minimum (for maximum topcoat hold up leave to dry overnight)

**Application Equipment Clean Up:** Clean all equipment using MIROSOL 1228 Thinner

**Shelf Life:** 24 months

**Packaging:** 1ltr, and 4 ltrs

#### Health & Safety

Before handling, refer to the Material Safety Data Sheet for health and safety information. Ensure that all personnel using this product have read and understood this data sheet and the associated MSDS and packaging label before using this product.

---

**Mirotone Pty Ltd Australia (Head Office)**  
ABN 40 000 041 136  
21 Marigold Street,  
Revesby NSW 2212 Australia  
P +61 2 9795 3700 F +61 2 9771 3601  
sales@mirotone.com.au

**Mirotone (NZ) Ltd New Zealand (Head Office)**  
32 Cryers Road, East Tamaki  
Auckland 2013 New Zealand  
P 0800 34 64 74 F 0800 34 64 34  
information@mirotone.co.nz

**Mirotone (Thailand) Co., Ltd**  
83 Moo 4, Poochaosamingprai Rd,  
Samrong Klang, Prapradaeng,  
Samutprakam, 10130, Thailand  
P +66 2 754 4451 F +66 2 754 4450

[www.mirotone.com](http://www.mirotone.com)