



NATUROIL 1499 Accelerator

NATUROIL 1499 Accelerator is a LEAD FREE, resin based drier.

Product Advantages

- Formulated to speed up drying time of Naturoil 1420 Tung Oil Sealer
- Minimise risk of frying of the next coating
- Environmentally Friendly LEAD FREE

Typical Applications

NATUROIL 1499 may be added to NATUROIL 1420 Tung Oil Sealer to reduce drying times.

Product Properties Typical Properties

Build: N/A Colour: N/A Sandability: N/A Gloss: N/A

Solvent Resistance: N/A
Water Resistance: N/A
Levelling & Flow: N/A

Product Approvals

NATUROIL 1499 has been evaluated for AS/NZS 4586:2004: Slip resistance classification of new pedestrian surface materials by Advanced Technology Testing & Research (ATTAR). The coating system passed the requirements of the "Dry Slip Resistance" and was classified as Dry = F. Certificates available on request.

Coverage:

Base coat:

Subsequent coats:

Coverage is dependent upon the porosity of the substrate.

Thinning:

Not required.

Application Methods:

To be added to speed up drying times of 1420.

Drying: Recoat:

Tack Free: Hard Dry: Full Cure:

Low temperatures and heavy film thickness will retard drying times. Direct sunlight and draft during drying may affect the final gloss level of the coating.

Recommended Sealers:

Application Equipment Clean Up: Clean all equipment using Mineral Turpentine. Ensure all cleaning products are removed before placing equipment back in the coating.

Shelf Life: 12 months, see label for use by date.

Packaging: 1 litre

Refer to the NATUROIL Product Information Guide for more information.

Health & Safety

Before handling, refer to the Material Safety Data Sheet for health and safety information. Ensure that all personnel using this product have read and understood this data sheet and the associated MSDS and packaging label before using this product.

Mirotone Pty Ltd Australia (Head Office) ABN 40 000 041 136 21 Marigold Street, Revesby NSW 2212 Australia P +61 2 9795 3700 F +61 2 9771 3601 sales@mirotone.com.au Mirotone (NZ) Ltd New Zealand (Head Office)
32 Cryers Road
East Tamaki
Auckland 2013, New Zealand
P 0800 34 64 74 F 0800 34 64 34
information@mirotone.co.nz

Mirotone (Thailand) Co., Ltd 83 Moo 4, Poochaosamingprai Rd, Samrong Klang, Prapradaeng, Samutprakam, 10130, Thailand P +66 2 754 4451 F +66 2 754 4450

www.mirotone.com

NATUROIL 1499 Issued 12 January 2018 Page 2

The information in this data sheet represents typical values. Application variables affect product performance therefore this information should be used as a guide. The user must satisfy themselves as to the suitability of this product for their requirements. Mirotone assumes no liability for use of this information.