

SOFTTOUCH

SOFTTOUCH is a clear water based two pack polyurethane in a matt finish with a soft touch effect.

Product Advantages

- Water based – low VOC (solvent content), non-flammable, low odour, low toxicity.
- Low yellowing coating to minimise colour change from exposure to UV.
- Very low gloss level
- Soft unique feel

Typical Applications

For use on interior solid wood & veneer surfaces in light to medium duty situations.

Application Equipment: Suction, Gravity, HVLP or Airmix. To improve atomisation smaller tips are recommended

Drying: Touch dry: 60-90 minutes at 25°C and 60% R.H
Stackable: vertically after 24 hours at 25°C and 60% R.H

Surface Preparation: Sand substrate with 150-180 grit paper. Apply FA42 2k clear sealer, leave to dry at least 4 hours at 25°C and 60% R.H, then lightly sand with 320 grit.

No. of coats: One (1)

Coverage: 100-130 gm/m²

Catalyst: Catalyse with CA 501 at 10% by weight under slow mechanical stirring then add Thinner #1

Thinning: Thin up to 10% with Thinner #1.

Pot Life: 3 hours at 20°C catalysed with CA 501.

Note: Do not use this product at temperatures below 10°C. Clean up application equipment with water.

Storage: Store at temperatures above 5° and below 35°C. Protect from frost.

Shelf Life: 12 months in correctly stored unopened containers.

Packaging: 5kg